



# Overseeder DZ Agri Air

*The highest yield per hectare  
and in hilly conditions*



## Supplied as standard with

- **Calibration tray.** Handy tool for the calibration test. Easy to store.
- **Gas strut.** Opens and closes the lid of the seed hopper smoothly.
- **LED lighting.** Clear, bright light ensures safe road transport and clear signals.
- **Platform.** Helps fill the machine safely.
- **Digital hectare counter.** Registers how many hectares have been sown.
- **Sight glass.** Shows the level in the seed hopper.
- **Universal dosing roller.** Enables accurate dosing of grass seeds (5-75 kg/ha).

## Added value options

- **Heavy cast iron packer ring roller.** Inhibits growth of problem grasses and promotes the shoot formation of good grasses.
- **Scraper for packer ring roller.** Ensures each moveable packer ring stays clean. Suitable for working in wet, heavy conditions.
- **Electronic Dosing System (EDS).** Dosing rate can be adjusted from the tractor cab, for example in bare patches or headlands. The system includes an electronic sensor that gives a clear acoustic and light signal when the seed hopper is empty.
- **Cam wheels for fine or coarse seed.** Enables small amounts of fine seed or large amounts of coarse seed to be sown.
- **TÜV equipment with LED lights.** Marker boards and lighting approved by German TÜV, incl. registration plate holder with lighting, ensure safe road transport.
- **Stone protection.** Prevents stones, clods and crop residues entering and blocking the discs.
- **Protection cover.** Protects the discs and keeps them clean. Prevents slaking and crusting of elements from the rear.

## Connections

- 1x double-acting valve
- 1x pressure-free return
- 12 Volt light connector

## Technical specifications

- Suitable for: grassland and hilly conditions
- Seed dosage: 3 - 190 kg per hectare (continuously adjustable)
- Sowing depth: 0-25 mm
- Working speed: 10-12 km per hour
- Hydraulic fan: max. 25 litres , 160 bar
- Discs: 2x sharp cutting discs Ø 406 mm and maintenance-free bearings
- Element: 11 cm progressive coil spring
- Turf guard: adjustable
- Pressure roller: 250-290 litres; height adjustable and refillable
- Calibration: calibration table and calibration tray
- Mounting: 3-point; CAT 2
- Depth adjustment: top link
- Row distance: 7.5 cm

Type	Roller	Weight	Seed hopper volume	Tractor power	GPS working width	Transport dimensions (lxwxh)
DZ 325.07.5	Smooth	1.200 kg	450 litre	80 hp	2.47 m	1.31 x 2.55 x 1.96 m.
DZ 325.07.5	Packer ring	1.970 kg	450 litre	90 hp	2.47 m	1.31 x 2.55 x 1.96 m.
DZ 329.07.5	Smooth	1.465 kg	450 litre	90 hp	2.85 m	1.31 x 2.95 x 1.96 m
DZ 329.07.5	Packer ring	2.115 kg	450 litre	100 hp	2.85 m	1.31 x 2.95 x 1.96 m

## Smooth roller compared with packer ring roller

### Smooth roller:

- Lighter in weight, but can be filled with water.
- Attractive price-quality ratio.
- Compacts soil and the cut.
- Levels rough surfaces.

### Packer ring roller:

- Follows the contours of the field perfectly as the rings (discs) move individually with a height variation of 5 cm.
- Individual discs press the cut from the side to optimally enclose seed in the soil.
- Inhibits growth of problem grasses (with short roots).
- Promotes shoot formation of good grasses.



Your fields, our passion