



Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

**Your fields,
our passion**

vredo.com

ART.NUMBER

DETAILS

C001123

VREDO PROFI XL 15.0M DV L

VREDO PROFI XL 15.0M DV L

-Construction year 2022

-Working width 18 m

-Travel distance 18.75 cm

-Vredo double disc system (408 mm diameter spoke discs)

-80 double discs

Maintenance-free mechanically sprung dual-disc elements

-Disc elements are steerable by means of torsion rubber

-Cassette seals and double-row bearings for maintenance-free disc bearings

-Easily replaceable wear parts such as discs, plastic slot block, steel drag feet, discharge rubber, etc.

-Pneumatic DropStop

-Equipped with black/white (I/O) 12V section switch, 20 sections, 75cm per section

-5-piece stable open support frame

-Automatic (hydraulic and mechanical) transport lock

-Mechanically operated automatic reflective warning signs according to DIN 11030 for shielding the sheaves during transport

-1 Lubrication point for central lubrication of the other joint parts

-Pendulum suspension for optimum ground adaptation where the side and middle frames can be freely pivoted by means of a push/pull rod

-Pendulum suspension is locked when lifting/folding (adjustable at the headland)

Ground adjustment adjustable by turning the push/pull rod on/off

-Meets the requirements of road transport legislation for the Netherlands and Germany, among others

-Wide rear panels

-Label holder with lighting

-2x Vogelsang ExaCut ECQ 48-40 distributor

-40 mm slurry discharge hoses

-stainless steel hose clamps on the slurry hoses and discharge rubbers

-LED lighting



Vredo

Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

Your fields,
our passion

vredo.com

