



**Vredo Dodewaard bv**  
Welysestraat 25a  
6669 DJ Dodewaard (NL)  
Tel. +31(0)488411254  
info@vredo.com

Your fields,  
our passion

[vredo.com](http://vredo.com)

ART.NUMBER	DETAILS
C001131	<p>VREDO ZB4 Profi XL 12M DV L</p> <p>VREDO ZB4 Profi XL 12M DV L Year of manufacture: 2022 Serial no.: 1025.016 Options: Multifaster 8-way coupling</p> <p>Specifications:</p> <ul style="list-style-type: none"><li>• Working width: 12 meters</li><li>• Row spacing: 18.75 cm</li><li>• Vredo single V-disc system (solid discs, 350 mm diameter)</li><li>• 64 discs</li><li>• Maintenance-free mechanically sprung dual disc knife holders</li><li>• Disc knife holders steerable via torsion rubbers</li><li>• Cassette seals and double-row bearings for disc bearing assembly</li><li>• Easily replaceable wear parts, such as discs and wear-resistant plastic guide blocks</li><li>• Pneumatic shut-off valves</li><li>• Equipped with 12V black-and-white section control, 16 sections of 75 cm</li><li>• 5-section open frame</li><li>• Automatic (hydraulic and mechanical) transport locking system</li><li>• Mechanically operated automatic disc protection with reflective elements for safety during transport; these enclose the discs when folding the injector</li><li>• Single connection for central lubrication of hinge points</li><li>• For optimal ground following, the frame can freely oscillate when unfolded in the field, as the folding/unfolding cylinders are linked by a push/pull rod in a parallelogram system</li><li>• Free oscillation with pendulum lock when the injector is folded (also adjustable when turning on the headland)</li><li>• Convex and flat adjustment, by extending or retracting the push/pull rod</li><li>• Complies with road transport legislation for, among others, the Netherlands and Germany</li><li>• Rear warning boards</li><li>• License plate holder with lighting</li><li>• 2x Vogelsang ExaCut ECQ 36-40 vertical distributors</li><li>• 40 mm manure hoses for precision fertilization</li><li>• Stainless steel hose clamps on manure hoses and outlet nozzles</li><li>• Transport width (lower side): 2.98 meters</li><li>• Transport width (upper side): 2.48 meters</li><li>• Height standing on the ground: 3.80 meters</li><li>• Estimated weight: approx. 3,350 kg</li><li>• LED lighting</li><li>• Detachable A-frame hitch</li></ul> <p>Required connections:</p> <ul style="list-style-type: none"><li>• 2x 1/2" hydraulic connections for folding/unfolding (open center)</li><li>• 1x air connection (red trailer coupling)</li><li>• 2x 3/4" distributor connections (open center). The distributor connection requires a continuous oil flow of 60 l/min</li><li>• 1x 1/2" pressure-free return</li><li>• 6" quick coupling manure hose connection on T-piece to distributors</li><li>• 1x connection for central lubrication from the towing vehicle</li><li>• 1x 16-pin Harting HAN connector for section control</li></ul>

# Vredo

Vredo Dodewaard bv  
Welysestraat 25a  
6669 DJ Dodewaard (NL)  
Tel. +31(0)488411254  
info@vredo.com

Your fields,  
our passion

[vredo.com](http://vredo.com)

