



Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

**Your fields,
our passion**

vredo.com

ART.NUMBER

DETAILS

G00100961

VREDO PROFI 9.0M DV H DEMO

Vredo Profi 9.0 DV H


- Machinenumber: 1020.001
- Year of construction: 2020
- Discs: 39cm

Specifications:

- Working width 9,0 meter
- Inter row distance 18,75 cm
- Vredo double V-disc system
- 48 pairs of discs
- Mechanic and suspended duo disc elements, free of maintenance
- Duo disc elements are mounted with torsion rubbers to be able to rotate/steer in a small angle
- Casette seals and double row ball bearings for disc bearings
- Easy to replace wear parts: discs, scraper blocks and steel turf guards
- Hydraulic dropstop
- Open constructed folding frame made out of 3 parts
- Automatic (hydraulic and mechanic) transport safety
- Automatic mechanic operated reflecting disc cover set for safe transport on the road
- 1 connection for central greasing of hinge points
- Frame has the possibility to lever in a free way thanks to the fact the hydraulic cylinders of in- and out folding are connected with each other by help of a parallelogram construction
- Parallelogram lever construction is locked in case hydraulic function of folding in is operated (adjustable for headland management)
- Leveling and unlevelling by way of adjusting the length of a special bar in the parallelogram construction
- Meets the requirements of the road transport legislation for the Netherlands and Germany
- Rear marking
- Registration plate holder incl. lightning
- 1x Vogelsang Dosimat DMX 50-40-800 distributor
- Slurry hoses 40mm, for precise distribution
- Stainless steel hose clamps on slurry hoses and rubber slurry outlets
- Transport width bottom: 2,98 m
- Transport width top: 2,48 m
- Height standing on the bottom: 3,80 m
- Weight ca. 2860kg
- LED lightning
- Platform and foldable access steps for Vogelsang distributor
- Demountable counterpart of A-frame`

Required connections:

- 2x 1/2" In/out folding (open center)
- 2x 1/2" dropstop (closed center)
- 2x 3/4" distributor (open center), distributor needs a continuous oil flow of 60L/min
- 1x 1/2" pressureless return line
- 6" KKV slurry hose connection
- 1x connection for central greasing supplied by vehicle





Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

**Your fields,
our passion**

vredo.com

