



Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

Your fields,
our passion

vredo.com

ART.NUMBER

DETAILS

G00101004

VREDO PROFI XL 18.0M DV L DEMO

Vredo Profi 18m DV L

- Machinenummer: 1030.002
- Year of construction 2021
- 24V
- Support wheels

Specifications:

- Working width 18 meter
- Inter row distance 18,75 cm
- Vredo double V-disc system
- 96 pairs of discs
- Mechanic and suspended duo disc elements, free of maintenance
- Duo disc elements are mounted with torsion rubbers to be able to rotate/steer in a small angle
- Cassette seals and double row ball bearings for disc bearings
- Easy to replace wear parts: discs, scraper blocks and steel turf guards
- Pneumatic dropstop
- Equipped with 12V I/O (Black/White) section control, 24 sections of 75cm each
- Open constructed folding frame made out of 7 parts
- Automatic (hydraulic and mechanic) transport safety
- Automatic mechanic operated reflecting disc cover set for safe transport on the road
- 1 connection for central greasing of hinge points
- Frame has the possibility to lever in a free way thanks to the fact the hydraulic cylinders of in- and out folding are connected with each other by help of a parallelogram construction
- Parallelogram lever construction is locked in case hydraulic function of folding in is operated (adjustable for headland management)
- Leveling and unlevelling by way of adjusting the length of a special bar in the parallelogram construction
- Meets the requirements of the road transport legislation for the Netherlands and Germany
- Rear marking
- Registration plate holder incl. lightning
- 2x Vogelsang ExaCut ECQ 48-40 vertical distributor
- Slurry hoses 40mm, for precise distribution
- Stainless steel hose clamps on slurry hoses and rubber slurry outlets
- Transport width bottom: 2,98m
- Transport width top: 2,82m
- Height standing on the bottom: 3,92m
- Weight ca. 5740kg
- LED lightning
- Demountable 3-point hitch connection

Required connections:

- 2x 1/2" In/out folding (open center)
- 2x 1/2" dropstop (closed center)
- 2x 3/4" distributor (open center), distributor needs a continuous oil flow of 30L/min
- 1x 1/2" pressureless return line
- 6" KKV slurry hose connection on T-piece to distributors
- 1x connection for central greasing supplied by vehicle
- 1x 24-P Harting HAN plug for section control
- 1x 3-P 12V plug for in/out folding (**fused at least 20A**)

Vredo

Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

Your fields,
our passion

vredo.com

