



Vredo Dodewaard bv  
Welysestraat 25a  
6669 DJ Dodewaard (NL)  
Tel. +31(0)488411254  
info@vredo.com

Your fields,  
our passion

vredo.com

## ART.NUMBER

## DETAILS

G00101048

VREDO VT7138

Vredo VT7138  
Machinenr. 0113.027  
Year: 2023  
Hours: +/- 5400H

### Technical Data

- Engine: Scania DC16 317A V8, 522 kW / 710 HP water-cooled
- EU Stage 5 with SCR (AdBlue) and DPF
- Maximum torque: 3320 Nm @ 1400 rpm
- Drive with Vredo VVT700 CVT Continuously Variable Transmission (CVT)
- Two speed ranges: 0-20 km/h and 0-40 km/h
- Reverse speed: 0-17 km/h
- Fuel tank: approx. 845 liters
- AdBlue tank: 69 liters
- Fully air-suspended Claas Comfort Cab, including radio/CD player with Bluetooth (with external microphone for phone calls)
- Fully automatic air conditioning
- Windshield wipers on the left and right sides of the cabin
- Control console in the right armrest of the seat, including driving and slurry system joystick and touchscreen terminal
- All vehicle and slurry system data on Hydac terminal
- Air-suspended Grammer Maximo Super-comfort seat
- Instructor seat
- Electrically adjustable and heated mirrors, including folding mirrors
- Efficient drivetrain through Ecomode
- Cruise control with load limit regulation
- Permanent all-wheel drive with lockable longitudinal differential in the transmission for the front axle and tandem rear axles
- Front and rear axles with lockable differential via pressure switch
- Steering: 6-wheel and dog-leg steering, 100% dog-leg on the 1st and 2nd axle, partial dog-leg on the 3rd axle
- Hydraulically suspended front axle with pendulum damping, rear axles with level control
- 3-point hitch, KAT 3 dimensions, double-acting lifting device at the rear, steering at dog-leg, torsion-suspended KAT 4 quick-coupling for implement suspension
- Active automatic ground adjustment with pressure or free-running, with distance control or float position
- Lift height: 660 mm, max. height approx. 1 m with 900 tires
- Lifting capacity at the ball: max. 105 kN (10.5 tons), continuous 75 kN (7.5 tons)
- Manual control for 3-point hitch on the rear fender of the vehicle, for detaching and attaching implements
- Automatic lubrication system with 4L grease reservoir
- 1 pump as a closed system max. 267 l/min, 420 bar, slurry pump drive
- 2 LS pumps, 170 l/min each at 200 bar, for external valves and internal functions such as steering, cooler drive, suspension, etc.
- 4 free DW/EW rear valves with control from the cabin
- Standard with free return 3/4"
- Reversing alarm
- Rear camera with LCD color monitor in the cabin with speaker
- Connection for an additional rear camera on the tractor



**Vredo Dodewaard bv**  
Welysestraat 25a  
6669 DJ Dodewaard (NL)  
Tel. +31(0)488411254  
info@vredo.com

**Your fields,  
our passion**

**vredo.com**

- Telescopic cylinder for tank tilting at the chassis
- 2 beacon lights on the cabin
- LED road lighting in the front underride protection
- 2 LED work lights on the rear fender of the cabin
- 2 LED work lights underneath the cabin
- 4 LED work lights on the cabin roof
- Air system connections for cabin and cooling system for cleaning
- Quick air connection at the rear of the tractor
- Fire extinguisher, 5 kg
- Vredo Trac comes standard with an emergency kit, including the most important fuses, pressure sensors, connectors, and O-rings
- Standard is a 2-year remote teleservice license on the machine (Vredo service can log into the machine to solve problems). After two years, the customer can purchase an additional license.

