



Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

Your fields,
our passion

vredo.com

ART.NUMBER

DETAILS

G00101066

Vredo VT4556

Vredo VT4556

Year: 2018

Operating hours: ± 6,400 h

Machine number: 0120.071

Options: John Deere GPS system, prepared for JD NIR

Engine & Performance

- Scania DC13 6-cylinder inline engine, 12.7 litre, water-cooled
- Output: 331 kW / 450 hp
- Max. torque: 2275 Nm at 1250 rpm
- EU Stage IV (T4f) with SCR (AdBlue) and EGR
- Continuously variable mechanical-hydraulic transmission 0–40 km/h
- Fuel tank: approx. 600 litres
- AdBlue tank: 60 litres

Cabin & Comfort

- Suspended comfort cabin on Koni dampers
- Fully automatic air conditioning
- Radio/CD with Bluetooth and external microphone
- Joystick control with touchscreen terminal
- Grammer Maximo air-suspended seat
- Electrically adjustable and heated mirrors
- Cruise control

Driveline & Chassis

- Switchable differential locks on front and rear axle
- Selectable 4-wheel drive
- 2 speed ranges: 0–20 km/h and 0–40 km/h
- Engine/hydrostatic brake
- 2-wheel, 4-wheel and crab steering
- Michelin 1000/55 R32 CEREXBIB tyres
- Suspended front axle with level control

Hydraulics & Linkage

- Rear 3-point linkage with automatic ground adaptation
- Automatic grease lubrication system
- Closed hydraulic system 177 l/min – 420 bar
- 3 LS pumps for hydraulics, PF unit and cooling
- 4 double-acting hydraulic valves

Safety & Lighting

- Reverse driving alarm
- Rear-view camera with LCD monitor
- 2 beacon lights
- LED road and work lights all around
- Air pressure cleaning system for cabin and cooler
- Fire extinguisher and emergency kit included

Tank VT4556 19500V



Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

**Your fields,
our passion**

vredo.com

- Polyester tank on steel frame with twistlocks
- Tank capacity: 19.5 m³
- Hydraulically tiltable for maintenance
- LED lighting and rear camera
- 2 inspection hatches
- Extra large mudguards

Pump Filter Unit PF9020

- Vogelsang VX186-390QD positive displacement pump – 9,000 l/min
- Vredo FT5200 cutting filter
- 8" suction arm, 120° swivelling
- 6" front suction connection, 160° swivelling
- Electrically/hydraulically operated
- Speed-independent dosing system
- Integrated LED lighting

